

WHAT IS CLAIMED IS:

1. An arrangement (10) for screening-off a space and preventing liquid from
splashing outside the space, comprising a plurality of lamellae or slats (11)
5 displaceable via an operating element, and having a first side (12), a second
side (13), short sides (22), a first longitudinal side (18) and a second
longitudinal side (19), the slats (11) being displaceable between a first
position screening-off the space and an open, second position,
characterised in
10 that the first longitudinal side (18) of the slat (11) is free; and that the slats
(11) are supported by at least one ladder (14) disposed at the second
longitudinal side (19), the slats (11) being vertically displaceable via
the operating element between the first position screening-off the
15 space and the open, second position, and the slats (11) being pivotal
about an axis which extends along the second longitudinal side (19)
and is substantially horizontal; and
- that the slats (11) are distributed along the ladder (14) with a mutual
20 spacing such that the first longitudinal side (18) of each respective slat
(11), in the screening-off first position, projects over the second
longitudinal side (19) of an adjacent slat (11).
2. The arrangement as claimed in Claim 1, wherein the ladder (14) runs
25 through a recess (20) in each respective slat (11), the recess (20) being
disposed at an edge portion of the second longitudinal side (19) of the slats
(11).
3. The arrangement as claimed in Claim 2, wherein the recess (20) projects
30 in to the slat (11) and is designed as a recess in and transversely of the
second longitudinal side (19) of the slat (11), so that the ladder (14) may be
moved into the recess (20) from the second longitudinal side (19).

4. The arrangement as claimed in any of the preceding Claims, wherein the ladder (14) includes abutments (27) projecting transversely of the extent of the ladder (14) for supporting the slats.
- 5 5. The arrangement as claimed in Claim 4, wherein a plurality of abutments (27) are distributed along the ladder (14) with a mutual spacing which is less than the width of each respective slat (11) so that the first longitudinal side (18) of each respective slat (11) in the screening-off first position, projects over the recess (20) in the second longitudinal side (19) of an adjacent slat (11).
- 10 (11).
6. The arrangement as claimed in Claim 5, wherein the abutment (27) is designed to be snapped in position in a groove (26) provided in the slat and corresponding to the abutment (27).
- 15
7. The arrangement as claimed in Claim 1, wherein the slats (11) include a projecting portion (17) for abutment against an adjacent slat (11) in the open, second position while forming an air gap (29) between adjacent slats (11).
- 20 8. The arrangement as claimed in Claim 7, wherein the projecting portion (17) is disposed at the second longitudinal side (19) of each respective slat (11).
9. The arrangement as claimed in Claim 7, wherein the projecting portion (17) is designed with a curvature so as to prevent liquid splashing from beneath.
- 25
10. The arrangement as claimed in Claim 1, wherein the slat (11) includes a bend (24, 25) designed for abutment against the operating element so as to prevent wear thereto.
- 30

11. The arrangement as claimed in any of the preceding Claims, wherein the screening-off first position is a raised position and the open, second position is a lowered position.

5 12. The arrangement as claimed in any of the preceding Claims, wherein the first space is a shower or bathing area.

13. The arrangement as claimed in any of the preceding Claims, wherein the arrangement (10) is a liquid-repellent Venetian blind or louver.

10

14. The arrangement as claimed in any of the preceding Claims, wherein the arrangement includes a cap (16) connected to the slats (11), the cap including a locking housing for locking the slats (11) in the open, second position.